

Control Valves

Three-way Mixing(Diverting) Control Valves



Three-way Mixing(Diverting) Control Valves

Three-way Mixing(Diverting)Control Valves are used in exchanger to adjust the fluid temperature. High precision and performance. Diverting type that divides the flow into two directions and mixing type that converges two flows into one are available.

This product complies with the GB/T4213-2008 standards.



Time Plate Technology Co., Ltd
In Taiwan

Type	Three-way, cast globe valve
Nominal size	DN25 ~ 450mm
Rated CV value	6.3 ~ 3100
Pressure rating	ANSI150 ~ 600 PN1.6 ~ 6.4MPa
Fluid Temperature	-45 ~ +566°C
End connections	Flanged : FF、RF、RJ、TG、MFM
Body & Bonnet Material	SCPH2/WCB,SCPH21/WC6,SCS13A/CF8,SCS14A/CF8M,SCS16A/CF3M,Ti and other alloy steels .etc.
Trim Material	SUS304,SUS304+Stellite,SUS316,SUS316+Stellite,SUS304L,SUS316L,Monel, Hastelloy C .etc.
Rangeability	30 : 1
Flow characteristics	Linear,EQ%
Leakage	ANSI Class IV
Actuator	HA Pneumatic Diaphragm type VA/VP Cylinder piston type EIL Electronic type M8 Intelligent type

Specifications



Time Plate Technology Co., Ltd
In Taiwan